Laboratory Study on Shear Strength of Soil using Woven and Non-woven Geotextiles

Yelvi¹, Aisyah Salimah¹, Vatih Abdullah¹ ¹Civil Engineering, Politeknik Negeri Jakarta, Depok 16424, Indonesia

Keywords: Geotextiles, Woven, Non-Woven, Shear Strength

Abstract: In constructing a construction, it is necessary to identify the type of soil as a place for the foundation and the building to rest on it. The carrying capacity of the soil also varies, in sand that has a uniform gradation when it is saturated, the shear strength will decrease. One way that can be done to increase the shear strength of the soil is to provide reinforcement with the addition of geotextiles. The shear strength parameters used in the planning of the bearing capacity of the soil reinforced by geotextiles are the internal friction angle and the interaction coefficient between the geotextile and the sand. The sample of this study used liquefaction potential sand Bangka using woven and non-woven geotextile reinforcement with a relative density variation of 25%, 50%, 75%. For use geotextiles are installed vertically and horizontally. To get the parameter value of shear strength, Direct Shear testing is carried out. Based on the test results, it is found that Bangka sand is uniform sand with values of Cu <6 and Cc <1. The increase in shear strength in the samples reinforced by geotextile vertically is greater than horizontally at a density of 25% and 50%, while at a density of 75% it states otherwise.

1 INTRODUCTION

Geotextiles have been widely applied in civil engineering projects with various functions. One of its functions is for reinforcement. Some examples of soil reinforcement with geotextiles are soil embankments, slopes, and retaining walls. Soil reinforcement with geotextiles requires knowledge of the soil-geotextile interface behavior for structural stability analysis (Day, 2000). In order to analyze the interface shear strength parameters, several studies have been conducted to understand the shear strength behavior of geotextile-reinforced sand soils. An significant factor in the design of geotextile structures is the interface shear strength. (Omar AH et al. 2019: Punetha et al. 2017; Wang et al. 2016; Brahim et al. 2016; Aldeeky et al. 2016; Hatami and Esmaili 2015; Vieira et al. 2015; Anubhav and Wu. 2015; Dixon and Jones 2005; Bergado et al. 2006). The results generally reveal that the addition of fibers to sandy soils as reinforcement can increase the shear strength compared to unreinforced sand. To improve performance in different soil conditions, strengthening the soil is increasingly important. The reinforcement mechanism is to withstand the soil's tensile deformation, thus increasing the overall

resistance of the composite soil matrix through the interface bond resistance limited by the tensile strength of the geotextile. Jewell (1996) has examined interaction between reinforced soil and the geotextiles. There are two conditions in soil interaction with reinforcement, namely direct shear and pull-out conditions. The results showed that the direct shear resistance is the ratio of the interface friction angle to the friction angle in the soil. The mobilization of the interface friction angle is one of the important factors affecting the stability analysis. Some researchers use the Direct Shear Test to understand the shear strength of reinforced soil behavior. The choice of direct shear test installation depends on the interaction mechanism to be reproduced. The reinforcement layer located parallel to the shear plane of the shear box offers laboratory test results in many literature studies. (Palmeira EM, 2008; Takasumi et al. 1991; Tan SA et al. 1998; Cerato AB and Lutenegger AJ 2006; Abu-Farsakh MY et al. 2007; Liu CN et al. 2009; Lopes ML, Silvano R 2010; Hossain B et al. 2012; Anubhav Basudhar PK 2013; Rifa'i, A., 2003; Tuna SC, Altun S 2012; Vieira CS, Lopes ML 2013; Kim D, Ha S 2014; Vangla P, Latha GM 2015; Choudhary AQ, and Krishna AM 2016. Other studies place the

58

Yelvi, ., Salimah, A. and Abdullah, V.
Laboratory Study on Shear Strength of Soil using Woven and Non-woven Geotextiles.
DOI: 10.5220/0010514700003153
In Proceedings of the 9th Annual Southeast Asian International Seminar (ASAIS 2020), pages 58-64
ISBN: 978-989-758-518-0
Copyright © 2022 by SCITEPRESS – Science and Technology Publications, Lda. All rights reserved

reinforcement layer perpendicular to the shear plane Jewell RA, Wroth CP 1987; Athanasopoulos GA 1993; Bauer GE, Zhao Y 1994; Palmeira EM 1999; Moayedi H et al. 2010; Saya~o ASFJ, Sieira ACCF 2012; Jose D et al. 2016. The reinforcement layer was positioned perpendicular to the shear plane in that study to characterize the behavior of the composite materials when the soil and reinforcement are shifted. Based on previous research which has given some evidence that the effect of geotextiles as reinforcement on the soil can increase the interface shear strength. However, not much research has been done on the effect of geotextile placement on sandy soil on the interface shear strength. Therefore, it is necessary to do more research on the effect of geotextile position on the soil on the interface shear strength. So it is hoped that the results of this study can add to the literature that can be used as a reference in geotextile reinforcement analysis to obtain the right design.

2 THEORY

Soil shears the resistance force exerted by soil grains against pressure or pull (Hardiyatmo, 2002). Based on this understanding, when the soil is exposed to freight, it will be held back by soil cohesion which depends on the type of soil and its density, but does not depend on the normal stresses acting on the shear plane and the friction between the grains of soil whose magnitude is directly proportional to the normal stress in the shear plane. Then the shear strength equation can be formulated as follows.

$$\tau = c + \sigma \tan \delta$$
(2.1)
(Note: $c = 0$ for sand and $\sigma = \sigma$ ')

For the shear strength which is strengthened by Geotextile, the determining parameters are the Mobilization of the Angle of Friction of the *interface* Sand-Geotextile (δ) and Adhesion (c_{sg}).

$$\tau = c_{sg} + \sigma_n \tan \delta \tag{2.2}$$

Determination of shear strength can be carried out Direct shear test utilizing controlled shear stress, where the addition of shear forces is made constant and regulated, or utilizing controlled stress in which the shear stress is applied by adding dead load sustainably, and with the same addition big every time, until it collapses.

3 METHOD

3.1 Soil

The soil sample used in the study was a disturbed sample by selecting Bangka sand which has a uniform gradation. On the soil, the grain size analysis test is conducted first to determine whether the soil is included in the soil criteria that have the liquefaction potential.

3.2 Geotextiles

Material as the interface consists of woven and nonwoven types. Woven type is GT 200 (GTX-N-2 High strength polyester) and non-woven type GT 250 PET. The characteristic of woven geotextile is a woven sheet with a polyester base material which has a uniform tensile strength. This type weights 200 gr / m2. The tensile strength value for the long direction is 4.15 kN / m and the transverse direction is 6.38 kN / m. Non-woven geotextile is a non-woven sheet that functions as separation, filtration, protection, and drainage. This type weights 250 gr / m2. The tensile strength value for the long direction is 8.87 kN / m and the transverse direction is 11.76 kN / m. The tensile strength test of the two types of geotextiles refers to the technical standard test ASTM D4595. Geotextile used is woven and non-woven can be seen in Figure 1.



Figure 1 Woven and Non-Woven Geotextiles

3.3 Sample Preparation and Testing Phase

3.3.1 Sample Preparation

The dry weight of sand is prepared for the relative density of 25%, 50%, and 75%, respectively. For sand

soil without geotextile reinforcement, the sand soil is directly put into the shear box. Then it is saturated and ready for the shear test. As for sand soil with geotextile, a sand-geotextile soil sample is prepared according to the position of the geotextile placement in the shear box. If the position is parallel to the sliding direction, then testing is carried out every one layer, two layers, and three layers. Meanwhile, if the direction is perpendicular to the sliding direction, only one layer is sufficient for each woven and nonwoven. After the sand-geotextile soil has been put into the shear box, it is saturated and ready for the shear test, then it is put into the shear box.

3.3.2 Testing Procedure

The test is divided into two stages. The first is testing to obtain the physical properties of the soil according to the provisions of the 1989 Annual Book of ASTM Standards and followed by testing the shear strength under static loads with the direct shear test. As many as 15 samples were made, namely sand without using geotextiles, sand using Woven and Non-Woven geotextiles which were installed horizontally and vertically. Each treatment had a different density, namely 25%, 50%, and 75%.

4 ANALYSIS AND DISCUSSION

The result of the Analysis of shieve, it shows that the sandy soil of Bangka the entry into an area that is potentially liquefied and can be seen in Figure 4.1

The USCS classification system is used to see the uniformity coefficient and curvature of grading. From the graph, it can be seen that the values of

$$D_{60} = 0.4, D_{10} = 0.15, D_{30} = 0.21$$

 $Cu = \frac{D_{60}}{D_{10}} = \frac{0.4}{0.15} = 2.666$

$$Cc = \frac{D_{30}^2}{D_{60} \times D_{10}} = \frac{0.21^2}{0.4 \times 0.15} = 0.735$$



Figure 2 Grading boundary curve between soils that have the potential for liquefaction (Tsuchida, 1970)

Well graded sand if Cu > 6 and 1 < Cc < 3, both criteria must be fulfilled, otherwise it is classified as poorly graded. From the Cu and Cc values obtained, Bangka sand is considered to be poorly graded with uniform gradations. The following is a summary of the Bangka sand soil property index which is presented in Table 1.

Table 1 Soil Property Index Soil

Properties	Value		
γd max	18.92 kN/m ³		
γd min	14.69 kN/m ³		
Gs	2.644		
e _{max}	0.799		
e _{min}	0.397		
D50	0.32 mm		
D10	0.15 mm		
D60	0.4 mm		
D30	0.21 mm		
Cu	2.666		
Сс	0.735		

Table 2 Results of the interaction coefficient between sand and geotextile (c_{sg})

	Relative Density (Dr%)		
Sample Treatment	25%	50%	75%
	c_{sg}	\mathbf{c}_{sg}	\mathbf{c}_{sg}
Woven Vertical	0.035	0.021	0.02
Horizontal Woven	0.032	0.021	0.01
Vertical Non- Woven	0.059	0.058	0.053
Horizontal Non- Woven	0.008	0.005	0.004

	Relative Density (Dr %)		
Sample Treatment	25%	50%	75%
	δ/φ	δ/φ	δ/φ
Without Geotextile	1	1	1
Vertical Woven	1.23	1.24	1.29
Horizontal Woven	1.29	1.28	1.24
Vertical Non- Woven	1.21	1.27	1.3
Horizontal Non- Woven	1.49	1.44	1.37

Table 3 Results Comparison of shear angle values after and before (δ and \emptyset) use of geotextiles

Based on the results of the shear test, the shear strength parameter is obtained, so that the equation used to obtain the shear strength value ($\tau f = \sigma \tan \varphi$) pure sand and $\tau = c_{sg} + \sigma \tan \delta$) for sand reinforced geotextile with the assumption of normal stress of 1 unit. Table 4 shows the results of the calculation of shear strength.

Table 4 The sand shear strength with the assumption of normal load 1 unit

Samula	25%	50%	75%
Treatment	τ (kg / cm ²)	$\tau (kg / cm^2)$	τ (kg / cm ²)
Without geotextile	0669	0615	0589
Woven vertical	0.681	0712	0.819
Woven horizontal	0717	0743	0767
Non- woven vertical	0696	0770	0861
Non- woven horizontal	0846	0851	0877



Figure 3 Graph relationship shear strength (kg / cm²) with sample tests on the density of 25%

Shear strength sand after the addition of geotextile on the density of a 25% increase, with strong maximum shear on samples of sand by geotextile non-woven horizontally by 0.846 kg/cm² and a minimum in samples of sand by woven geotextile vertically by 0.681 kg/cm².

The increase in the pure shear strength with vertical woven geotextile reinforced sand was 1.8%, and the pure sand with horizontal woven geotextile reinforced sand was 7.2%. Pure sand with sand reinforced with non-woven geotextiles vertically by 4.1% and pure sand with sand reinforced by horizontal non-woven geotextiles by 26%. The horizontal use of geotextiles indicates a greater increase than the use of vertical geotextiles based on data on the increase in sand shear intensity at a density of 25%.



Figure 4 Graph of the relationship of shear strength (kg / cm^2) with the Test Sample at a density of 50%.

The shear strength of sand after the addition of geotextiles at a density of 50% has increased, with the maximum shear strength in sand samples given horizontal non-woven geotextiles of $0.851 \text{ kg}/\text{cm}^2$ and minimum sample was woven geotextile sand by vertically by 0.712 kg / cm².

The increase in pure shear strength with vertical woven geotextile reinforced sand was 15.7%, pure sand with horizontal woven geotextile reinforced sand was 20.8%. pure sand with vertical sand reinforced by non-woven geotextiles by 25.2% and pure sand with horizontal non-woven geotextile reinforced sand by 38.3%. Based on the data on the increase in the shear strength of sand at a density of 50%, the horizontal use of geotextiles shows a greater increase than the use of vertical geotextiles.



Figure 5 Graph of the relationship of shear strength (kg / cm^2) with the Test Sample at a density of 75%

The Shear strength of sand after the addition of geotextiles at a density of 75% has increased, with the maximum shear strength in sand samples given horizontal non-woven geotextiles of 0.877 kg/cm² and minimum sample by woven geotextile sand horizontally by 0.767 kg / cm².

The increase in pure shear strength with vertical woven geotextile reinforced sand was 39%, and the pure sand with horizontal woven geotextile reinforced sand was 30.2%. Pure sand with vertical sand reinforced by non-woven geotextiles amounting to 46.2% and pure sand with horizontal non-woven geotextile reinforced sand by 48.9%. Based on the data on the increase in the shear strength of sand at a density of 75%, the average increase in the use of geotextiles vertically shows a greater increase than the use of horizontal geotextiles, namely 42.6% versus 39.6%.

5 CONCLUSION

Based on the actual results of this research, it can be inferred as follows:

- Shear strength of pure sand or without geotextile reinforcement decreases with each increase in the average relative density of 6.15%
- 2. Vertical has an increase with each addition of relative density by an average of 9.75%.
- 3. The shear strength of sand that is reinforced with woven geotextiles installed horizontally has an

increase with each addition of an average relative density of 3.4%.

- 4. The shear strength of sand that is reinforced with non-woven geotextiles installed vertically has an increase with each addition of an average relative density of 11%.
- 5. The shear strength of sand that is reinforced with non-woven geotextiles installed horizontally increases with each addition of an average relative density of 1.8%.
- 6. The increase in shear strength in geotextile reinforced samples vertically is greater than horizontally at a density of 25% and 50%, whereas at a density of 75% states the opposite.

ACKNOWLEDGMENTS

The authors would like to sincerely thank the Head of UP2M Jakarta State Polytechnic for providing support for this research through the PNJ DIPA funding. The authors also honor the PNJ Department of Civil Engineering's Head of Laboratory for granting permission to use laboratory facilities..

The Geotextiles were provided by PT Mitra Hijau Lestari, Indonesia. We highly appreciate this support.

REFERENCES

- Abu-Farsakh MY, Coronel J, Tao M (2007) Effect of soil moisture content and dry density on cohesive soilgeosynthetic interactions using large direct shear tests. J Mater Civ Eng 19(7):540–549
- Aldeeky, H., O. Al Hattamleh, and B. A. Alfoul. 2016. "Effect of Sand Placement Method on the Interface Friction of Sand and Geotextile." International Journal of Civil Engineering 14 (2): 133–138. doi:10.1007/s40999-016-0019-0.
- Anubhav Basudhar PK (2013) Interface behaviour of woven geotextile with rounded and angular particle sand. J Mater Civ Eng ASCE 25(12):1970–1974
- Anubhav, W. H. 2015. "Modelling of Non-linear Shear Displacement Behaviour of Soil–Geotextile Interface." International Journal of Geosynthetics and Ground Engineering 1: 19. doi:10.1007/s40891-015-0021-7
- Abu-Farsakh MY, Coronel J, Tao M (2007) Effect of soil moisture content and dry density on cohesive soil– geosynthetic interactions using large direct shear tests. J Mater Civ Eng 19(7):540–549
- Aldeeky, H., O. Al Hattamleh, and B. A. Alfoul. 2016.
 "Effect of Sand Placement Method on the Interface Friction of Sand and Geotextile." International Journal of Civil Engineering 14 (2): 133–138. doi:10.1007/s40999-016-0019-0.

- Anubhav Basudhar PK (2013) Interface behaviour of woven geotextile with rounded and angular particle sand. J Mater Civ Eng ASCE 25(12):1970–1974
- Anubhav, W. H. 2015. "Modelling of Non-linear Shear Displacement Behaviour of Soil–Geotextile Interface." International Journal of Geosynthetics and Ground Engineering 1: 19. doi:10.1007/s40891-015-0021-7
- Athanasopoulos GA (1993) Effect of particle size on the mechanical behaviour of sand-geotextile composites. Geotext Geomembr 12(3):255–273
- Bauer GE, Zhao Y (1994) A realistic stress transfer model for geogrids in pullout. In: Proceedings of the 5th International Conference on Geotextiles, Geomembranes and Related Products, vol 1. Singapore, pp 457–460
- Bergado, D. T., G. V. Ramana, H. Sia, and I. Varun. 2006. "Evaluation of Interface Shear Strength of Composite Liner System and Stability Analysis for a Landfill Lining System in Thailand." Geotextiles and Geomembranes 24 (6): 371–393. doi:10.1016/j.geotexmem.2006.04.001
- Brahim, A., A. Arab, M. Belkhatir, and I. Shahrour. 2016. "Laboratory Study of Geotextiles Performance on Reinforced Sandy Soil." Journal of Earth Science 27: 1060. doi:10.1007/s12583-015-0621-0
- Cerato AB, Lutenegger AJ (2006) Specimen size and scale effects of direct shear box tests of sands. Geotech Test J 29(6):1–10. doi:10.1520/GTJ100312
- Choudhary AQ, Krishna AM (2016) Experimental investigation of interface behaviour of different types of granular soil/geosynthetics. Int J Geosynth Ground Eng 2(1):1–11. doi:10. 1007/s40891-016-0044-8
- Day, R.W., 2000, Geotechnical Engineer's Portable Handbook, Mc Graw Hill, New York
- Dixon, N., and D. R. V. Jones. 2005. "Engineering Properties of Municipal Solid Waste." Geotextiles and Geomembranes 23 (3): 205–233. doi:10.1016/j.geotexmem.2004.11.002.
- Hatami, K., and D. Esmaili. 2015. "Unsaturated Soil Woven Geotextile Interface Strength Properties from Small-scale Pullout and Interface Tests." Geosynthetics International 22 (2): 161–172. doi:10.1680/ gein.15.00002.
- Hossain B, Hossain Z, Sakai T (2012) Interaction properties of geosynthetic with different backfill soils. Int J Geosci 3:1033–1039. doi:10.4236/ijg.2012.35104
- Jewell RA, Wroth CP (1987) Direct shear tests and reinforced sand. Ge'otech 37(1):53–68
- Jewell, R.A., 1996, Soil Reinforcement with Geotextiles, CIRIA, London
- Jose D., Infante U., Martin GAM, Ariel P. Eberhardt M., (2016), Shear Strength Behavior of Different Geosynthetic Reinforced Soil Structure from Direct Shear Test, Int. J. of Geosynth. and Ground Eng. (2016) 2:17, Springer International Publishing Switzerland.
- Kim D, Ha S (2014) Effects of particle size on the shear behaviour of coarse grained soils reinforced with geogrid. Mater 7:963–979. doi:10.3390/ma7020963

- Liu CN, Ho YH, Huang JW (2009) Large scale direct shear tests of soil/PET-yarn geogrid interfaces. Geotext Geomembr 27:19–30
- Lopes ML, Silvano R (2010) Soil/geotextile interface behavior in direct shear and pullout movements. Geotech Geol Eng 28:791–804
- Moayedi H, Huat BBK, Kazemian S, Asadi A (2010) Optimization of tension absorption of geosynthetics through reinforced slope. Electron J Geotech Eng 15(2):93–104. Available at the website ejge.com at http://www.ejge.com/2010/Ppr10.010/Ppr10.010.pdf
- Omar AH, Samer R, Hussein dan Husam AQ. (2019). Evaluating aqaba marine sand geotextile interface shear strength, International Journal of Geotechnical Engineering,

https://doi.org/10.1080/19386362.2019.1651985

- Palmeira EM (1999) Execution and interpretation of laboratory tests on geosynthetic material (in Portuguese). In: Proceedings of the 1st south-American symposium on geosynthetics, ABMSISSMGE, vol 1. Rio de Janeiro, pp 87–108
- Palmeira EM (2008) Soil-geosynthetic interaction: modeling and analysis. Geotext Geomembr 27(5):368– 390
- Punetha, P., P. Mohanty, and M. Samanta. 2017. "Microstructural Investigation on Mechanical Behavior of Soil-geosynthetic Interface in Direct Shear Test." Geotextiles and Geomembranes 45 (3): 197–210. doi:10.1016/j.geotexmem.2017.02.001.
- Rifa'i, A., (2003), Perilaku Interaksi Tanah-Geotekstil Terhadap Parameter Kuat Geser, dinamika TEKNIK SIPIL, Volume 9, Nomor 1, Januari 2009 : 92 – 100, Yogyakarta.
- Saya[°]o ASFJ, Sieira ACCF (2012) Evaluation of direct shear tests on geogrid reinforced soil. Soils Rocks 35(1):65–74
- Takasumi DL, Green KR, Holtz R (1991) Soilgeosynthetics interface strength characteristics: a review of state-of the-art testing procedures. In: proceedings of the geosynthetics'91 conference, Atlanta 1:87–100
- Tan SA, Chew SH, Wong WK (1998) Sand-geotextile interface shear strength by torsional ring shear tests. Geotext Geomembr 16(3):299–328
- Tuna SC, Altun S (2012) Mechanical behaviour of sandgeotextile interface. Sci Iran 19(4):1044–1051
- Vangla P, Latha GM (2015) Influence of particle size on the friction and interfacial shear strength of sands of similar morphology. Int J Geosynth Ground Eng 1(6):1–12. doi:10.1007/ s40891-014-0008-9
- Vieira CS, Lopes ML (2013) Soil-geosynthetic interface shear strength by simple and directshear tests. In: Proceedings of the 18th international conference on soil mechanics and geotechnical engineering, Paris 1:3497– 3500
- Vieira, C. S., M. L. Lopes de, and L. Caldeira. 2015. "Sandnonwoven Geotextile Interfaces Shear Strength by Direct Shear and Simple Shear Tests." Geomechanics and Engineering 9 (5): 601–618. doi:10.12989/ gae.2015.9.5.601.

ASAIS 2020 - Annual Southeast Asian International Seminar

Wang, J., F. Y. Liu, P. Wang, and Y. Q. Cai. 2016. "Particle Size Effects on Coarse Soil-geogrid Interface Response in Cyclic and Post-cyclic Direct Shear Tests." Geotextiles and Geomembranes 44 (6): 854–861. doi:10.1016/j.geotexmem.2016.06.011

